

# Durafloor Plus PUR

Commercial Vinyl Sheet Flooring



**nuplex**<sup>®</sup>

Construction Products

[www.nuplexconstruction.co.nz](http://www.nuplexconstruction.co.nz)

# Durafloor Plus PUR

## Commercial Vinyl Sheet Flooring



538 Sapphire



540 Atlantis



534 Charcoal



537 Bermuda



539 Aegean



533 Dolphin



536 Marina



550 Spring



547 Truffle



552 Sky



541 Herb



535 Frost

These are representative samples. For technical reasons shade and pattern may vary.



549 Terracotta



544 Straw



532 Arctic



548 Cayenne



545 Hessian



531 Ice



551 Canary



543 Champagne



542 Ivory





546 Cocoa

# Durafloor Plus PUR

## Commercial Vinyl Sheet Flooring

**nuplex**

Construction Products



Durafloor Plus is a homogeneous floorcovering suitable for use in commercial areas. Available in sheet and tile form. A versatile pattern in 22 fresh colourways. Durafloor Plus is equipped with PUR surface for protection and easier initial maintenance. The PUR also provides a better base for future maintenance procedures.

### Technical Data

Type of flooring	EN 649	Homogeneous single layered vinyl flooring
CE certification / Country of origin		Yes / EU Manufactured
Classification	EN 685	Commercial: 34 Industrial: 43
Wear layer thickness	EN 429	2,0 mm
PUR		Yes
Total thickness	EN 428	2,0 mm
Total weight/m <sup>2</sup>	EN 430	3700 g
Dimensional stability	EN 434	= 0,40 % for rolls = 0,25 % for tiles
Abrasion: Thickness loss Volume loss	EN 660: Part 1 EN 660: Part 2	Group M: = 0,30 mm Group M: = 7,5 mm3
Residual indentation	EN 433	Approx. 0,06 mm
Castor chair test	EN 425	Suitable
Static electrical charge	EN 1815	< 2 kV
Underfloor heating		Suitable - max. 27°C
Impact sound resistance	EN ISO 717/2	Approx. + 4 dB
Thermal resistance	EN 12667/DIN 52612	Approx. 0,01 m <sup>2</sup> K/W
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl,s1 = 8 kW/m <sup>2</sup> Pass
Light fastness	EN ISO 105-B02	= Level 6
Chemical resistance	EN 423	Good resistance
Fungi and Bacteria resistance	DIN EN 846-A/C	Does not favor growth
Slip resistance	DIN 51130 EN 13893	R9 = 0,3
Colours		22
Form of delivery	EN 426 Sheet	Rolls: 2m x 20m x 2mm thick

#### Post Installation Finishing:

Durafloor is finished with a polyurethane coating which reduces initial cleaning requirements and provides a foundation for an ongoing maintenance regime. Excessive surface damage or wear during the construction period or during in-use may require the immediate use of protective floor polishes. Due to the unpredictable nature of wear on floors, Nuplex generally recommend the use of applied polishes during cleaning regimes to ensure an undamaged long life.

#### Adhesives and sub-floor Preparation:

Adhesives: Nuplex Duracryl, HSV, or Truestik VA1.  
Levelling compounds: FLC, Durabond Superfine, NC160 self leveller., NC880

#### Warranty:

A 10 year product warranty applies if the product is installed to specification and if a relevant cleaning and polish system is observed.

Nuplex instructions regarding installation, cleaning and maintenance should be observed.  
Please contact Nuplex at the address shown for these instructions.

Sheet Code	Weld Rod Code	Sheet Code	Weld Rod Code	Sheet Code	Weld Rod Code	Sheet Code	Weld Rod Code
BMV 531	BMWR 531	BMV 537	BMWR 537	BMV 543	BMWR 543	BMV 549	BMWR 549
BMV 532	BMWR 532	BMV 538	BMWR 538	BMV 544	BMWR 544	BMV 550	BMWR 550
BMV 533	BMWR 533	BMV 539	BMWR 539	BMV 545	BMWR 545	BMV 551	BMWR 551
BMV 534	BMWR 534	BMV 540	BMWR 540	BMV 546	BMWR 546	BMV 552	BMWR 552
BMV 535	BMWR 535	BMV 541	BMWR 541	BMV 547	BMWR 547		
BMV 536	BMWR 536	BMV 542	BMWR 542	BMV 548	BMWR 548		

