




Altro K30 Altro Stronghold™ 30

Safety Flooring / Suelos de Seguridad /
Sicherheitsbodenbelag


Altro K30
Altro Stronghold™ 30
contains recycled material

Altro is the first safety flooring
manufacturer to recycle
traditional safety flooring in-house

All Altro safety flooring
contains recycled content




Monsoon K30153
WR81 / A1M81 / LRV58




Dolphin K3010
WR86 / A1M86 / LRV51




Abyss K3001
WR100 / A1M100 / LRV31




Oyster K30215
WR20 / A1M20 / LRV65




Skyline K30332
WR52 / A1M52 / LRV55




Tundra K30500
WR153 / A1M239 / LRV52




Camel K3017
WR64 / A1M239 / LRV58




Surf K30412
WR71 / A1M71 / LRV54




Lagoon K30910
WR39 / A1M34 / LRV33



Maple K30522
WR24 / A1M27 / LRV65



Russet K30262
WR41 / A1M41 / LRV47




















Velvet K30365
WR256 / A1M148 / LRV33

Exact Material Match with samples cannot be guaranteed



Altro K30 Altro Stronghold™ 30 safety flooring

Flooring Type Tipo de pavimento Belagsart		EN 13845/ EN 13553	Safety flooring Suelo de seguridad antideslizante Sicherheitsbodenbelag
Classification for use Areas de uso Einsatzbereiche		EN 685	34 & 43 34 y 43 34 & 43
Slip Resistance Resistencia al deslizamiento Rutschsicherheit*		TRRL / CTE EN 13845 EN 13893 DIN 51130	> 45. Class 3 / Close 3 / Klasse 3 (CTE) ES DS R12
Thickness Espesor Total Gesamtdicke		EN 428	3 mm
Wear Layer Capa de uso Nutzschicht		EN 429	3 mm
Weight Peso Flaechengewicht		EN 430	3.4 kg/m ² 3,4 kg/m ² 3,4 kg/m ²
Roll Dimensions Dimensiones del rollos Rollenabmessungen		EN 426	2 m x 15 m = 30 m ²
Light Fastness Resistencia a la luz Lichtechtheit		EN 20105-B02	>6
Sound Insulation Aislamiento acustico Trittschal		ISO 140-8	10 dB
Wear Resistance Abrasion VerschleiBverhalten		EN 13845 EN660-2	Group 34/43, Grupo 34/43 / Gruppe 34/43 Group T / Grupo T / Gruppe T
Indentation Punzonamiento Resteindruck		EN 433	< 0.10mm
Fire Performance Reaccion al fuego Brandverhalten		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl s1 >8kw/m ² Pass Close Bfl s1 >8kw/m ² Conforme Klasse Bfl-s1 >8kW/m ² , bestanden
Chemical Resistance Resistencia a los productos quimicos Chemikalieneinwirkung**		EN 423	Good Buena bestandig
Castor Chair Abrasion Huellas de sillas de ruedas Stuhlrollenbeanspruchung		EN 425	Pass Conforme geeignet
Under floor heating Calefaccion por el suelo FuBbodenheizung		EN 12667	Suitable Apto geeignet
Electrical Behaviours Carateristicas electricas Elektrisches Verhalten		EN1815	< 2 kw Antistatic < 2kw antistatisch
VOC Emissions Emisiones de VOC VOC Emissionen		prEN 15052 Section 01350	Low/Pass/gering Baja/Conforme gering/geeignet

*For wet areas where bare foot slip resistance is required such as showers and swimming pool surrounds, we recommend the use of Altro Marine T20

** Caution Ketone/Aromatic Solvents, Please contact Altro for further technical advice regarding staining and chemical resistance.

Contains Biocide

Installation and Maintenance

All Installations in accordance with Altro safety flooring instructions and Local Codes of Practice. Please refer to Altro Cleaning Card for maintenance advice. Failure to install and maintain Altro floors in accordance with installation instructions can affect its performance and slip resistance. Floors should be protected from other trades,



For further technical information please visit www.altro.com

altro

Manufactured by:
Altro Ltd, Works Road
Letchworth Garden City
SG6 1NW, United Kingdom