




altro



Reef T20801




Cascade IPT20809



Spa T20802




Crest T20805




Rainfall IPT20810



Shower T20804




Torrent T20806



Tide IPT20808



Steam IPT20807



Ripple T20803



Altro Whiterock™ is frequently specified to complement Altro Marine for shower/wet areas.

The complete hygienic flooring & walling solution.

Altro Marine™ 20

versatile collection / safety flooring

Altro Marine 20

For a seamless appearance, matching weldrods and mastics are available.
N.B. Exact colour match with samples cannot be guaranteed.

explore **altroism** at www.altro.com



New look Altro Marine. Taking wet area safety floors to a higher level of design.

This carefully textured 2mm thick surface is specifically designed for safety with wet, bare feet or soft soled footwear. It is ideal for shower and drying areas, swimming pool and whirlpool surrounds, swimming pool changing rooms and other wet areas requiring slip resistance.

Standards and Accreditation

Meets and exceeds the requirements of BS EN 649 / EN 13845.

Slip Resistance

Greater than or equal to 36; low risk of slipping (UK Slip Resistance Guidelines with TRRL Rubber). Class B DIN51097.

The construction of Altro safety flooring ensures that its slip resistance is maintained throughout the life of the product.

Specification

Format	Roll	
Dimensions	20m x 2m	(EN426)
Thickness	2.0mm	(EN428)
Weight	2.6 kg/m ²	(EN430)

Performance

Indentation	<0.1mm	(EN433)
Dimensional stability	<0.4%	(EN434)
Flexibility	PASS 20mm mandrel	(EN435)
Colour fastness	>6	(EN 20105 B02)
Fire performance	Class 1	BS476: Part 7
	Pass	(EN ISO 11925-2)
	>8kW/m ²	(EN ISO 9239-1)
	Class B ₁ s1	(EN13501-1)
	Pass	(EN425)
Abrasion/wear resistance		
Classification	Classes 34/43	(EN685)
	Homogeneous	
Sound absorption	13dB	(ISO 140-8)

Warranties

Warranty 7 years
(subject to conditions on warranty form attached to every roll of Altro safety flooring).

Life expectancy 15+ years
(under many traffic conditions, wear is comparable to epoxy and quarry tiles).

Chemicals

Resists Common dilute acids, alkalis and many organic solvents
Caution Ketone solvents.

N.B. More information on performance and standards is available in Altro flooring and walling brochures or on www.altro.com

Staining

Certain chemicals may cause staining of vinyl. Traffic stain can be caused by oil residue, certain cleaning agents, asphalt and anti-oxidants in some types of rubber. For further information or advice, please contact Altro.

Biological

Excellent surface antibacterial activity due to bacteriostat incorporation*.

*Please consult Altro Technical Services for further information.

versatile collection / safety flooring Altro Marine 20



altro

our promise to deliver



the highest quality products & services



Resilient
Flooring
Range of
the Year
(6th year running)

Materials of Composition

Matrix	High quality vinyl
Inclusions	Natural aggregates throughout; Coloured quartz - surface layer, coloured vinyl chips
Backing	Non-woven polyester/cellulose, glass fibre reinforcement
Wear layer	2mm

Recommended Cleaning Methods

Machine or hand scrubbing and Altroclean 44™ or other Altro approved cleaners. Technical advances to Altro safety floors significantly improve their cleaning characteristics. Refer to Altro safety flooring routine maintenance instructions for comprehensive cleaning advice and chemicals on www.altro.com or contact 01462 707600.

Installation and Maintenance

All installations in accordance with Code of Practice BS 8203:2001, and Altro safety flooring installation instructions.

Joints	All hot-welded. A range of complementary weldrods and mastics are available
Subfloor	As Code of Practice, with effective DPM where necessary
Adhesives	As recommended in Altro safety flooring installation instructions, the Altro price list or at www.altro.com

N.B. Failure to install and maintain Altro flooring in accordance with Altro safety flooring installation instructions' can affect its performance and slip resistance. Floors should be protected from other trades and thoroughly cleaned before handover.

Altro Flooring and Walling Ranges

Products include safety flooring, smooth flooring, resin systems, Mondo rubber, sports flooring, hygienic wall coatings, hygienic PVCu walling and ceiling systems, hygienic doorsets, decorative wall coatings and protective wall coatings. For more information ask for the Altro Flooring and Walling Solutions brochures appropriate to your industry sector, or visit www.altro.com

Sample Specification

The slip resistant vinyl sheet flooring to be Altro safety flooring Marine 20, thickness 2.0mm, width 2000mm, colour (...), as manufactured by Altro. All flooring to be hot welded and laid according to the manufacturer's instructions with recommended adhesives and sealants.

NBS model specification is available for downloading on www.altro.com or telephone 01462707600.

Prior to specification please ensure you are referring to the most recent sample card.



To obtain individual samples use the SampleExpress service. Please quote the product range and product name/number. Larger samples are also available but may take a few days.

Explore Light. Explore Colour.
Explore Mood. At www.altro.com

explore altroism at www.altro.com

Altro Limited, Works Road, Letchworth Garden City, Hertfordshire SG6 1NW Tel: 01462 707600 Fax: 01462 707515 e-mail: enquiries@altro.com

Altro, Altro Marine, Altro Whiterock and SampleExpress are trademarks of Altro Limited.