

Eclipse PUR

Commercial Vinyl Sheet Flooring



nuplex[®]

Construction Products

www.nuplexconstruction.co.nz

Eclipse PUR

Commercial Vinyl Sheet Flooring



BMVES502KP
Cappuccino



BMVES503KP
Elephant



BMVES504KP
Honey



BMVES505KP
Biscuit



BMVES506KP
Skin



BMVES507KP
Cocoa



BMVES508KP
Lilac



BMVES509KP
Atlantic



BMVES510KP
Herb



BMVES511KP
Eco Green



BMVES512KP
Jet



BMVES514KP
Granite

These are representative samples. For technical reasons shade and pattern may vary.



BMVES516KP
Azure



BMVES518KP
Terracotta



BMVES526KP
Ice



BMVES536KP
Chamois



BMVES555KP
Frost



BMVES556KP
Clear Blue



BMVES559KP
Eden



BMVES562KP
Beach



BMVES565KP
Chilli Red



BMVES567KP
Surf

Eclipse PUR

Commercial Vinyl Sheet Flooring

nuplex

Construction Products



Eclipse PUR is a homogeneous, high quality vinyl flooring suitable for most types of premises such as schools healthcare facilities and other types of public buildings. Eclipse PUR needs no additional surface treatment such as polish or wax when exposed to normal wear and tear. This will have a beneficial effect on life cycle cost. The Eclipse PUR range includes 22 harmonious colours.

Technical Data

Type of flooring	EN 649	Homogeneous vinyl flooring
CE certification / Country of origin		Yes / EU Manufactured
Classification	EN 685	Commercial: 34 Industrial: 43
Wear layer thickness	EN 429	2,0 mm
Surface treatment		PUR reinforced
Total thickness	EN 428	2,0 mm
Total weight/m ²	EN 430	3150 g
Dimensional stability	EN 434	≤ 0.4 % for rolls
Abrasion: Thickness loss	EN 660: Part 1	Group P: ≤ 0.15mm
Volume loss	EN 660: Part 2	Group P: ≤ 4.00mm ³
Residual indentation	EN 433	Approx. 0,06 mm
Castor chair test	EN 425	Suitable
Static electrical charge	EN 1815	< 2 kV
Underfloor heating		Suitable - max. 27°C
Flexibility	EN 435	Okay
Impact sound resistance	EN ISO 717/2	Approx. + 4 dB
Thermal resistance	EN 12667/DIN 52612	Approx. 0.01m ² K/W
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl,s1 ≤ 8 kW/m ² Pass
Light fastness	EN ISO 105-B02	≤ Level 6
Chemical resistance	EN 423	Good resistance
Fungi and Bacteria resistance	DIN EN 846-A/C	Does not favor growth
Slip resistance	DIN 51130 EN 13893	R9 ≤ 0.3
Colours		22
Form of delivery	EN 426 Rolls	Rolls: 2m x 23m x 2mm

Adhesives and sub-floor Preparation:

Adhesives: Nuplex Duracryl, Supacryl or Truestik VA1.

Levelling compounds: Nuplex FLC, Durabond Superfine, NC160 self leveller, NC888,Ultrafinish

Warranty:

A 10 year product warranty applies if the product is installed to the Nuplex specification and if the relevant initial cleaning and after care procedures are followed.

Nuplex instructions regarding installation, cleaning and maintenance should be observed. Please contact Nuplex at the address shown for these instructions.

Sheet Code	Weld Rod Code	Sheet Code	Weld Rod Code	Sheet Code	Weld Rod Code	Sheet Code	Weld Rod Code
BMVES502KP	BNWRBO	BMVES508KP	BNWRL	BMVES516KP	BNWRMB	BMVES559KP	BNWRPG
BMVES503KP	BNWRK	BMVES509KP	BNWRDB	BMVES518KP	BNWRLO	BMVES562KP	BNWRYP
BMVES504KP	BNWRLBR	BMVES510KP	BNWRMGG	BMVES526KP	BNWRPW	BMVES565KP	BNWRRL
BMVES505KP	BNWRLS	BMVES511KP	BNWRBGG	BMVES536KP	BNWRLB	BMVES567KP	BNWRLBL
BMVES506KP	BNWRT	BMVES512KP	BNWRDG	BMVES555KP	BNWRMG		
BMVES507KP	BNWRDDB	BMVES514KP	BNWRMG	BMVES556KP	BNWRCB		



ISO 9001