

TECHNICAL DATA

Technical data may be updated at any time. It is the users responsibility to check data validity by reference to the website or Nuplex Construction Products

MANUAL SECTION	ISSUE DATE	AUTHORISED	REPLACES	PAGE
Vinyl	May 2008	LN	Aug 2007	1 of 2

Wall-iT Wall lining Vinyl Sheet

Tech-Data & Cleaning Instructions:

Wall-iT is a sheet vinyl for the protection of vertical wall surfaces. Vinyl sheet wall claddings offer the following advantages:

- High Durability
- High appearance retention
- High abrasion resistance
- Impact resistance from trolleys etc.

These linings are often used in the following situations:

- Hospital corridors and patient rooms
- Rest-home walkways
- Stairwells
- Bathroom walls

Wall-iT specification:

Width: 2m
 Roll length: 30m
 Thickness: 1.3mm
 Color: Off white (Spanish white).
 Faint directional pattern
 Description: Very flexible, non-cracking



Installation:

Wall-iT sheets can be laid vertically or horizontally to minimise joints. In the latter case the pattern will run horizontally as well.

Install using contact adhesive (CS110 or CB103). It can also be installed using HSV Acrylic adhesive. Once installed, the joints can be heat welded or chemically seamed.

After installation carefully clean and protect to avoid damage prior to handover.

.....cont. **Cleaning Instructions**

No warranty either expressed or implied or statutory is made by NUPLEX in this document except as expressly stated in any sale and purchase agreement entered into between NUPLEX and the buyer. CERTIFIED ISO 9001 REG. NO. 158 This document is a technical data information sheet The description of the product or products and the properties of the product or products contained in this document is for the sole purpose of identifying the product or products and describing their property or properties and does not constitute a warranty that the product or its properties shall conform to that description; nor is the description of the product and/or its properties a warranty by NUPLEX that the goods are suitable for a particular purpose.

Wall-iT Wall Lining Vinyl Sheet

Cleaning and Maintenance Instructions

Wall-iT is a homogeneous wallcovering with a PU – Polyurethane coating. This makes the surface easier to clean and therefore improves hygiene.

Cleaning

Clean the wall with a damp sponge or cloth. Use a neutral floor cleaner (ph 7–9).

Limescale can be removed using a white scouring cloth and a more acidic cleaner (ph 2-4). Rinse or wipe off with clean water.

Heavily soiled surfaces can be cleaned using a white nylon scourer and an alkaline detergent (ph 9–10). Rinse or wipe off with clean water. A rubber squeegee is recommended for shower areas.

NOTE: Always follow the chemical manufacturer's instructions.

Machine -cleaning

Steam cleaning is good for removing marks and for cleaning in corners and other awkward places. Ideally, spray the area with detergent, allow a few minutes for it to work, then remove the dirt using steam. Rinse the surfaces with clean water.

High – pressure washing is also an efficient method for large areas as well as awkward places.

Marks

If possible, take action while marks are fresh. Use a white nylon scourer and a neutral floor cleaner, methylated spirits or cleaning spirit. Rinse or wipe off with clean water.

Never use solvents because they damage the surface.